

U.S. DEPARTMENT OF COMMERCE/ National Oceanic and Atmospheric Administration

OFCM



OFFICE OF THE FEDERAL COORDINATOR FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH

FEDERAL METEOROLOGICAL HANDBOOK NO. 11

DOPPLER RADAR METEOROLOGICAL OBSERVATIONS

PART A
SYSTEM CONCEPTS,
RESPONSIBILITIES, AND
PROCEDURES

FCM-H11A-2004



Washington, DC
March 2004

THE FEDERAL COMMITTEE FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH (FCMSSR)

VADM CONRAD C. LAUTENBACHER, JR., USN (RET.)
Chairman, Department of Commerce

VACANT
Office of Science and Technology Policy

DR. RAYMOND MOTHAS
Department of Agriculture

BRIG GEN DAVID L. JOHNSON, USAF (RET.)
Department of Commerce

MR. ALAN SHAFFER
Department of Defense

DR. ARISTIDES PATRINOS
Department of Energy

DR. ROBERT M. HIRSCH
Department of the Interior

MR. RALPH BRAIBANTI
Department of State

MR. RANDOLPH LYON
Office of Management and Budget

MR. JAMES H. WASHINGTON
Department of Transportation

MR. ANTHONY LOWE
Federal Emergency Management Agency
Department of Homeland Security

DR. GHASSEM R. ASRAR
National Aeronautics and Space
Administration

DR. MARGARET S. LEINEN
National Science Foundation

MR. PAUL MISENCIK
National Transportation Safety Board

MR. JACK R. STROSNIDER
U.S. Nuclear Regulatory Commission

MR. HENRY L. LONGEST (Acting)
Environmental Protection Agency

MR. SAMUEL P. WILLIAMSON
Federal Coordinator

MR. JAMES B. HARRISON, Executive Secretary
Office of the Federal Coordinator for
Meteorological Services and Supporting Research

THE INTERDEPARTMENTAL COMMITTEE FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH (ICMSSR)

MR. SAMUEL P. WILLIAMSON, Chairman
Federal Coordinator

MR. THOMAS PUTERBAUGH
Department of Agriculture

MR. JOHN E. JONES, JR.
Department of Commerce

RADM STEVEN J. TOMASZESKI, USN
United States Navy
Department of Defense

BRIG GEN THOMAS E. STICKFORD, USAF
United States Air Force
Department of Defense

MR. RICKEY PETTY
Department of Energy

MR. LEWIS T. MOORE
Department of the Interior

MR. JEFFREY MACLURE
Department of State

VACANT
Federal Aviation Administration
Department of Transportation

DR. JONATHAN M. BERKSON
United States Coast Guard
Department of Homeland Security

DR. S. T. RAO
Environmental Protection Agency

MR. JOHN GAMBEL
Federal Emergency Management Agency
Department of Homeland Security

DR. RAMESH KAKAR
National Aeronautics and Space
Administration

DR. JARVIS MOYERS
National Science Foundation

MR. DONALD E. EICK
National Transportation Safety Board

MS. LETA A. BROWN
U.S. Nuclear Regulatory Commission

MS. ERIN WUCHTE
Office of Management and Budget

MR. JAMES B. HARRISON, Executive Secretary
Office of the Federal Coordinator for
Meteorological Services and Supporting Research

FEDERAL COORDINATOR FOR
METEOROLOGICAL SERVICES AND SUPPORTING RESEARCH

DOPPLER RADAR
METEOROLOGICAL OBSERVATIONS

FEDERAL
METEOROLOGICAL
HANDBOOK NO. 11
MARCH 2004

PART A
SYSTEM CONCEPTS, RESPONSIBILITIES,
AND PROCEDURES

FCM-H11A-2004

Washington, DC

CHANGE AND REVIEW LOG

Use this page to record changes and notices of reviews.

Change Number	Page Numbers	Date Posted	Initials
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			

Changes are indicated by a vertical line in the margin next to the change.

Review Date	Comments	Initials

PREFACE

The Federal Coordinator for Meteorological Services and Supporting Research has the responsibility to maintain and publish Federal Meteorological Handbooks. This series of documents provides standards and procedures to facilitate the efficient collection, sharing, and use of meteorological information by agencies of the federal government and private industry.

Federal Meteorological Handbook, Number 11 (FMH-11), DOPPLER RADAR METEOROLOGICAL OBSERVATIONS, was prepared and published under the auspices of the Office of the Federal Coordinator for Meteorological Services and Supporting Research (OFCM) at the request of the Next Generation Weather Radar (NEXRAD) Program Council (NPC) and in coordination with the federal agencies that are represented on the Interdepartmental Committee for Meteorological Services and Supporting Research (ICMSSR). The purpose of FMH-11 is to standardize, insofar as practical, the operation of the Weather Surveillance Radar -1988, Doppler (WSR-88D) systems and the procedures used by personnel of the Departments of Commerce, Defense, and Transportation. By approving publication of this handbook, those agencies have agreed to operate their WSR-88D systems accordingly. Some flexibility under certain meteorological, siting, or mission circumstances is permitted to enhance the quality and utility of some WSR-88D products.

The revision process is dependent on the evolution of WSR-88D subsystems software, and products. Part A has been revised twice to ensure it provides users current operations guidance. Parts B, C, and D are being revised in a separate effort principally through the guidance of the Radar Operations Center (ROC), formerly known as the Operational Support Facility (OSF). All revisions are coordinated among the NEXRAD triagencies, thus they possess the same authority as the initial edition of FMH-11.

The agencies shall review the documents at least annually. The goal is to review/update the handbooks with every WSR-88D software build (6-month release cycle). Suggestions for modifications and additions shall be forwarded through the appropriate channels in each agency for consideration, and issuance, if appropriate. Changes may be issued as write-in corrections, page replacement or additions, or a total reprint when necessary. Each major part of the FMH-11 is designed to stand alone, except where cross references avoid voluminous redundancy. Changes should be annotated in the Change and Review Log near the beginning of each part.

In all, FMH-11 has four parts:

- Part A - System Concepts, Responsibilities, and Procedures (March 2004)
- Part B - Doppler Radar Theory and Meteorology (June 1990)
- Part C - WSR-88D Products and Algorithms (February 1991)
- Part D - WSR-88D Systems Description and Operational Applications (April 1992)

Part A provides an introduction for the entire Handbook including the restatement of some policy, definitions of terms, and agencies' functions and responsibilities under the WSR-88D System Concept. It provides current listings of the general location of systems; prescribes the relative priorities for product generation, so as to assure availability to all users; and sets requirements for national archiving. Additionally, authority for change to adaptation parameters is established. Familiarity with Part A should aid the user of other parts of FMH-11 and provide a better understanding of the overall WSR-88D system.

Samuel P. Williamson
Federal Coordinator for Meteorological
Services and Supporting Research

FEDERAL METEOROLOGICAL HANDBOOK NO. 11
 DOPPLER RADAR METEOROLOGICAL OBSERVATIONS
 PART A
 SYSTEM CONCEPTS, RESPONSIBILITIES, AND PROCEDURES

TABLE OF CONTENTS

	Page
CHANGE AND REVIEW LOG	ii
PREFACE	iii
TABLE OF CONTENTS	v
LIST OF TABLES	vii
DEFINITION OF TERMS	ix
CHAPTER 1. BACKGROUND	
1.1 Introduction	1-1
1.2 Purpose and Scope	1-1
1.3 Policy	1-1
1.4 Changes	1-2
CHAPTER 2. WSR-88D SYSTEM CONCEPT	
2.1 Overview of Agency Functions	2-1
2.1.1 Department of Commerce	2-1
2.1.2 Department of Defense	2-1
2.1.3 Department of Transportation	2-1
2.2 System Support Management	2-2
2.3 Memorandum of Agreement for the Interagency Operation of the WSR-88D	2-2
2.4 External User Access to WSR-88D Data and Products	2-2
2.4.1 Products and Product Data	2-2
2.4.2 Wideband Access	2-2
2.5 National Centers' Applications	2-2

CHAPTER 3.	SITE RESPONSIBILITIES	
	3.1	Introduction 3-1
	3.2	Network Site Responsibilities 3-1
	3.3	Supplemental Site Responsibilities 3-1
	3.4	Non-Network Site Responsibilities 3-2
CHAPTER 4.	OPERATIONAL MODES, VOLUME COVERAGE PATTERNS, AND PRODUCTS	
	4.1	Introduction 4-1
	4.2	Operational Modes 4-1
	4.2.1	Mode A -- Precipitation Mode 4-2
	4.2.2	Mode B -- Clear-Air Mode 4-2
	4.3	Volume Coverage Patterns 4-2
	4.3.1	Volume Coverage Patterns 31 and 32 4-2
	4.3.2	Volume Coverage Patterns 11 and 21 4-2
	4.3.3	Volume Coverage Pattern 12 4-2
	4.3.4	Volume Coverage Pattern 121 4-2
	4.4	WSR-88D Product Suite 4-3
CHAPTER 5.	ARCHIVING	
	5.1	Introduction 5-1
	5.2	Archive Level I 5-1
	5.3	Archive Level II 5-1
	5.4	Archive Level III 5-1
	5.5	Archive Level IV 5-1
	5.6	Retention by National Climatic Data Center 5-2
CHAPTER 6.	ADAPTABLE PARAMETER CHANGE AUTHORITY	
	6.1	Introduction 6-1
	6.2	Levels of Change Authority 6-1
	6.2.1	Radar Operations Center 6-1
	6.2.2	Unit Radar Committee 6-2
	6.2.3	Agency 6-2
APPENDIX A.	ACRONYMS AND ABBREVIATIONS	A-1
APPENDIX B.	GLOSSARY	B-1

LIST OF TABLES

Table		Page
3-1.	Network Sites	3-3
3-2.	Supplemental Sites	3-8
3-3.	DOT Non-CONUS Sites	3-9
3-4.	DOD Non-CONUS Sites	3-9
3-5.	Calculation of Antenna Elevation	3-10
4-1.	Volume Coverage Pattern Description	4-3
4-2.	Product Description	4-4

This Page Intentionally Left Blank

Definition of Terms

WSR-88D System. A WSR-88D system is composed of a Weather Surveillance Radar - 1988 Doppler, and communications links to distribute products to various agency display systems. The functional designations are: Radar Data Acquisition (RDA) system, Radar Product Generator (RPG), and agency user display systems.

Agency User Display Systems. The agencies have various user display systems with dedicated and/or dial connections to WSR-88Ds. The current list of systems are:

Principal User Processor (PUP). The original display system fielded with the WSR-88D. Currently only used at some DoD locations.

Open Principal User Processor (OPUP). This new DoD display system is fielded in three sizes: small, medium, and large.

Advanced Weather Interactive Processing System (AWIPS). The NWS operates AWIPS at each Weather Forecast Office to integrate and display data and products from all sources.

Weather and Radar Processor (WARP). The FAA computer network that places WSR-88D product data on air controllers' displays in Air Route Traffic Control Centers (ARTCCs). The WARP also collects, formats, and distributes weather information to Center Weather Service Units at FAA ARTCCs.

Integrated Terminal Weather System (ITWS). This FAA system integrates data from the WSR-88D, Terminal Doppler Weather Radar, Airport Surveillance Radar-9 (ASR-9), Low-level Windshear alert systems (LLWAS), Automated Surface Observing Systems (ASOS), and other NWS systems.

Medium Intensity Airport Weather System (MIAWS). This FAA system will go into airports that have a medium intensity of aircraft operations.

Micro Enroute Air Route Traffic System (Micro-EARTS). This FAA system is located at Combined Center/RAPCON (CERAP) outside the CONUS.

National Weather Radar Network. The national weather radar network consists of sites dispersed throughout the conterminous United States (CONUS).

Network Site. A Network Site is a Department of Commerce WSR-88D site in the CONUS.

Supplemental Site. A Supplemental Site is a Department of Defense site in the CONUS.

Non-Network Site. A non-Network Site is a non-CONUS Department of Defense site or a non-CONUS Department of Transportation site.

Principal User. Principal users are the National Oceanic and Atmospheric Administration (NOAA) National Weather Service, the Air Force, the Naval Meteorology and Oceanography Command, the Marine Corps Weather Service, and the Federal Aviation Administration.

Associated Principal User. An associated principal user is a principal user linked to a WSR-88D system with a dedicated telecommunication line.

Non-Associated Principal User. A non-associated principal user is a principal user with access to a WSR-88D system through means of dial telecommunication.

External User. An external user is anyone other than a principal user who is authorized access to WSR-88D data and products, e.g., information service companies, broadcast meteorologists, aviation interests, marine interests, industrial meteorologists, other government agencies, and universities.

CHAPTER 1

BACKGROUND

1.1 Introduction. The impetus for originally preparing this handbook was the development, acquisition, and deployment of the Weather Surveillance Radar - 1988, Doppler (WSR-88D). The motivation of this update is to reflect the changing operation of the WSR-88D system as it matures.

The Federal Coordinator for Meteorological Services and Supporting Research determined that the preparation of this handbook was required to support triagency utilization of the WSR-88D. Subsequent to coordination within the Interdepartmental Committee for Meteorological Services and Supporting Research (ICMSSR), a Doppler Radar Meteorological Observations Working Group (WG/DRMO) was formed within the Committee for Basic Services. The WG/DRMO was charged with the responsibility for preparation of this Federal Meteorological Handbook, Number 11 (FMH-11).

The WG/DRMO was composed of personnel from the National Weather Service within the Department of Commerce, the Air Force Weather Agency and the Naval Meteorology and Oceanography Command within the Department of Defense, and the Federal Aviation Administration within the Department of Transportation. This version has been coordinated with the triagency WSR-88D focal points and triagency Radar Operations Center personnel.

1.2 Purpose and Scope. This handbook provides information, guidance, and instruction regarding the triagency management and operation of the WSR-88D systems. The following definitions apply throughout this handbook:

Shall: means that a procedure or practice is mandatory.

Should: means that a procedure or practice is recommended.

May: means that a procedure or practice is optional.

Will: means futurity, not a requirement to be applied to a procedure or practice.

1.3 Policy. The WSR-88D systems shall be operated to satisfy the integrated set of federal requirements that emanated primarily from the public charters of the departments represented in the Next Generation Weather Radar (NEXRAD) Program Council (NPC) and the NEXRAD Program Management Committee (NPMC). This handbook has been developed to establish standards for the triagency operation of the WSR-88D systems and the collection, processing, and dissemination of information to meet those requirements. As a federal system, it shall be operated to meet as many requirements as possible. However, this handbook guides operations to fulfill first those fundamental requirements of the agencies that founded the program. Policy, procedures, and operational concepts, as defined in this handbook, shall be adhered to by the principal user agencies.

1.4 Changes. All recommendations for modifications of this handbook shall be forwarded to the OFCM for consideration and coordination through the ICMSSR infrastructure. No modification shall be adopted that adversely impacts fulfillment of the integrated requirements that drove the development of the program without the consent of the NPC. (The NPC has delegated this responsibility to the NPMC.)

CHAPTER 2

WSR-88D SYSTEM CONCEPT

2.1 Overview of Agency Functions. The following sections provide discussions of each principal user agency's functions with regard to WSR-88D system operations.

2.1.1 Department of Commerce. Within the Department of Commerce (DOC), the National Weather Service (NWS) is the civilian meteorological agency of the Federal Government. As such, it must fill a broad spectrum of meteorological and hydrological requirements in its efforts to protect life and property and support the economy of the United States (U.S.). Specifically, NWS is responsible for the detection and public warning of hazardous weather such as tornadoes, severe thunderstorms, hurricanes, floods, flash floods, winter storms, damaging tides, and any other meteorological or hydrological event with possible harmful effects. NWS provides weather information for marine operations covering offshore, coastal, Great Lakes, and river and harbor areas for both commercial and recreational activities. NWS also routinely provides forecasts for civilian aviation, reservoir regulation, wildland fire fighting agencies, and a variety of commercial activities. To assist in fulfilling these responsibilities, NWS operates the national weather radar network and uses information from Department of Defense (DOD) and Department of Transportation (DOT) WSR-88D systems.

2.1.2 Department of Defense. Within the Department of Defense (DOD), the U.S. Air Force provides worldwide meteorological and aerospace environmental services to the Air Force, Army, and certain other DOD elements; the Naval Meteorology and Oceanography Command provides meteorological and oceanographic support to the Navy and oceanographic support to the DOD; and the Marine Corps Weather Service Units provide environmental support to U.S. Marine Corps activities and operations. These organizations are responsible for providing and relaying severe weather warnings for the protection of DOD resources and personnel, managing flood control reservoirs (U.S. Army Corps of Engineers), providing meteorological and space environmental information to aid the decision-making process at all levels of command authority, and supporting military aerospace operations. To meet these responsibilities, DOD operates WSR-88D systems in the United States and overseas and uses information from the DOC and DOT WSR-88D systems.

2.1.3 Department of Transportation. The Department of Transportation (DOT), through the Federal Aviation Administration (FAA), is responsible for the safe and efficient utilization of the National Airspace System. In meeting this responsibility, DOT disseminates information on the location and intensity of potentially hazardous weather conditions to pilots, air traffic controllers, air traffic flow management, and others concerned with aviation. DOT obtains and processes data from DOC, DOD, and DOT WSR-88D systems for use by DOT personnel and DOC personnel located in DOT facilities.

2.2 System Support Management. Operational support for the deployed WSR-88D system is provided by the Radar Operations Center (ROC), formerly known as the Operational Support Facility (OSF), located in Norman, Oklahoma. The ROC provides centralized management, coordination, and control for the comprehensive life cycle support of WSR-88D systems. The ROC performs systematic and coordinated analyses of the day-to-day operations and maintenance of WSR-88D systems to determine the need for improvement and provides both immediate and long-term support during the WSR-88D life cycle.

2.3 Memorandum of Agreement for the Interagency Operation of the WSR- 88D. Policies, procedures, and operational concepts, as defined in this handbook, have been agreed to by each principal user agency. Each agency shall endeavor to support, to the highest degree possible and in accordance with the terms of the Memorandum of Agreement (MOA) for the Interagency Operation of the WSR-88D, the data, product, and operational requirements of the other agencies. This supportive service shall be consistent with the capabilities and mission priorities of the agency that has received the request for support. The MOA also forms the basis for the membership, leadership, and activities of the Unit Radar Committee (URC) that shall be at each WSR-88D site where more than one NEXRAD agency is connected.

2.4 External User Access to WSR-88D Data and Products. Real-time access to data and products can be achieved through two methods. Products and product data can be obtained through the NWS' Radar Product Central Collection Dissemination Service (RPCCDS). The Level II data can be obtained through the NWS Level II Data Collection and Distribution Network.

2.4.1 Products and Product Data. The RPCCDS replaced the NEXRAD Information Dissemination Service (NIDS) agreement in January 2001. The RPCCDS makes a predefined subset of all WSR-88D products available in near real time from every WSR-88D in the CONUS and all but four remote DOD non-CONUS locations available to external users. Users will be able to connect to the RPCCDS via a dedicated connection or file transfer protocol (FTP). Local NWS weather forecast offices will provide a predetermined subset of the images available from their WSR-88D on their WEB site. In addition, a predetermined set of products will be provided to NOAAPORT users.

2.4.2 Wideband Access. The principal user agencies offer wideband access on a limited basis to support government operations at sites where the required interface hardware is installed. Non-NEXRAD agency connections to individual radar sites will not be permitted. Only certified systems will be permitted to connect to radars.

The NWS has established a WSR-88D Level II Data Collection And Distribution Network. The network initially (March 2004) includes all NWS radars (121) and 3 CONUS DOD radars. By March 2005 the remaining 18 CONUS DOD radars will be added to the network. These data are available in near real time from many sources and can be used or redistributed without any restriction. Information on the network is available at: http://www.roc.noaa.gov/NWS_Level_2/.

2.5 National Centers' Applications. The national centers of the NWS, Air Force, and FAA have agency-specific display platforms to acquire and display real-time WSR-88D data for their agency-specific applications. Several dial ports per RPG are allocated for national centers'

access. National centers may require information to suit a wide range of missions that assist decision making in support of critical operations and exercises. The FAA's center has access to Doppler weather radar information from a variety of sources to support its management of aviation traffic flow. The national centers are: Storm Prediction Center (SPC), Tropical Prediction Center (TPC), Marine Prediction Center (MPC), Aviation Weather Center (AWC), Hydrometeorological Prediction Center (HPC), Air Force CONUS and Pacific Operational Weather Squadrons (OWSs), River Forecast Centers (RFC), and Air Traffic Control Systems Command Center (ATCSCC).

This Page Intentionally Left Blank

CHAPTER 3

SITE RESPONSIBILITIES

3.1 Introduction. The WSR-88D system is vital to the operation of each principal user agency. Therefore, WSR-88D systems shall be operated to satisfy the integrated needs of all three agencies. Each agency shall endeavor to support, to the maximum extent possible, the data, products, and operational requirements of the others, consistent with the capabilities and mission priorities of that agency. The units shall be operated in accordance with the procedures described in this handbook and as agreed to by the URC within the terms of the MOA for the Interagency Operation of the WSR-88D.

WSR-88D sites are categorized as Network, Supplemental, or non-Network. Tables 3-1 through 3-4 list the metropolitan areas served by each system. In addition, the WSR-88D system four-letter International Civil Aviation Organization (ICAO) identifier; name of RDA system location; and RDA antenna elevation in feet above mean sea level (MSL); are specified for each system. Table 3-5 shows how the antenna elevation above MSL is computed.

3.2 Network Site Responsibilities. A WSR-88D Network Site (Table 3-1) shall:

- C Operate continuously, 24 hours per day, and collect, collate and make available via narrowband communications, radar data and products in support of the national weather radar network. This support shall be performed in accordance with the policies described in this handbook and such agreements as may be made among the principal users, including the MOA for Interagency Operation of the WSR-88D. A copy of the MOA may be obtained at the following URL: <http://www.roc.noaa.gov/MOA.pdf>.
- C Use one of the operational modes and volume coverage patterns agreed to by the URC.
- C Generate and distribute WSR-88D products as specified by *WSR-88D Operator Handbook, Guidance on Adaptable Parameters-RPG*. The handbook can be obtained at the following URL: <http://www.roc.noaa.gov/ssb/sysdoc/Operations.asp>.
- C Use appropriate levels of clutter filtering to reduce ground clutter and anomalous propagation.

3.3 Supplemental Site Responsibilities. A WSR-88D Supplemental Site (Table 3-2) shall:

- C Operate continuously, 24 hours per day, and collect, collate, and make available via narrowband communications, radar data and products in support of the DOD. This support shall be performed in accordance with the policies described in this handbook and such agreements as may be made among the principal users, including the MOA for Interagency Operation of the WSR-88D. A copy of the MOA may be obtained at the following URL: <http://www.roc.noaa.gov/MOA.pdf>.
- C Use one of the operational modes and volume coverage patterns agreed to by the URC.

- C Provide assistance to NWS forecast offices and the FAA by providing access to weather radar data to reduce gaps in the national weather radar network. Ensure the provision of radar data is consistent with responsibilities stated in the MOA for Interagency Operation of the WSR-88D.
- C Generate and distribute WSR-88D products as specified by *WSR-88D Operator Handbook, Guidance on Adaptable Parameters-RPG*. The handbook can be obtained at the following URL: <http://www.roc.noaa.gov/ssb/sysdoc/Operations.asp>.
- C Use appropriate levels of clutter filtering to reduce ground clutter and anomalous propagation.

3.4 Non-Network Site Responsibilities.

A DOT non-CONUS Site (Table 3-3) shall:

- C Operate continuously, 24 hours per day, and collect, collate, and make available via narrowband communications, radar data and products in support of FAA's enroute weather radar coverage, DOD and NWS's operations. This support shall be performed in accordance with the policies described in this handbook and such agreements as may be made among the principal users, including the MOA for Interagency Operation of the WSR-88D. A copy of the MOA may be obtained at the following URL: <http://www.roc.noaa.gov/MOA.pdf>.
- C Use one of the operational modes and volume coverage patterns agreed to by the URC.
- C Generate and distribute WSR-88D products as specified by *WSR-88D Operator Handbook, Guidance on Adaptable Parameters-RPG*. The handbook can be obtained at the following URL: <http://www.roc.noaa.gov/ssb/sysdoc/Operations.asp>.
- C Use appropriate levels of clutter filtering to reduce ground clutter and anomalous propagation.

A DOD non-CONUS Site (Table 3-4) shall:

- C Operate continuously, 24 hours per day, and collect, collate, and make available via narrowband communications, radar data and products in support of the DOD. This support shall be performed in accordance with the policies described in this handbook and such agreements as may be made among the principal users, including the MOA for Interagency Operation of the WSR-88D. A copy of the MOA may be obtained at the following URL: <http://www.roc.noaa.gov/MOA.pdf>.
- C Use one of the operational modes and volume coverage patterns agreed to by the URC.
- C Generate and distribute WSR-88D products as specified by *WSR-88D Operator Handbook, Guidance on Adaptable Parameters-RPG*. The handbook can be obtained at the following URL: <http://www.roc.noaa.gov/ssb/sysdoc/Operations.asp>.
- C Use appropriate levels of clutter filtering to reduce ground clutter and anomalous propagation.

**TABLE 3-1
NETWORK SITES**

Metropolitan Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
AL, Birmingham	KBMX	Alabaster, AL	759
AL, Mobile	KMOB	Mobile Regional Airport	289
AL, Northeast AL	KHTX	Hyttop, AL	1,860
AR, Western AR	KSRX	Chaffee Ridge, AR	721
AR, Little Rock	KLZK	N. Little Rock Municipal Airport	649
AZ, Flagstaff	KFSX *	Flagstaff, AZ	7,515
AZ, Phoenix	KIWA	Phoenix, AZ	1,418
AZ, Tucson	KEMX	Tucson, AZ	5,319
AZ, Yuma	KYUX *	Yuma, AZ	237
CA, Santa Ana Mts.	KSOX	Santa Ana Mtns: Beeks Place	3,092
CA, Eureka	KBHX	Bunker Hill: Humboldt Cnty	2,516
CA, Los Angeles	KVTX	Sulphur Mtn.: Ventura Cnty	2,807
CA, Sacramento	KDAX	USAF Davis: Sacramento, CA	144
CA, San Diego	KNKX	Miramar Naval Air Station	1,052
CA, San Francisco	KMUX	Los Gatos, CA	3,550
CA, San Joaquin	KHNX	Hanford Municipal Airport	341
CO, Denver	KFTG	Front Range Airport	5,611
CO, Grand Junction	KGJX*	Grand Mesa: Mesa, CO	10,056
CO, Pueblo	KPUX	Pueblo, CO	5,314
FL, Jacksonville	KJAX	Jacksonville Intl. Airport	130
FL, Key West	KBYX	Boca Chica Key, FL	89
FL, Melbourne	KMLB	Melbourne Regional Airport	116
FL, Miami	KAMX	Richmond Heights	112
FL, Tallahassee	KTLH	Tallahassee Regional Airport	177
FL, Tampa Bay Area	KTBW	Ruskin, FL	122

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

* - Redundant RDA

**TABLE 3-1
NETWORK SITES**

Metropolitan Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
GA, Atlanta	KFFC	Peachtree City, GA	972
IA, Des Moines	KDMX	Johnston, IA	1,095
IA, Quad Cities	KDVN	Davenport Municipal Airport	851
ID, Boise	KCBX	Wild Horse Corral, Ada City	3,142
ID, Pocatello	KSFX	Springfield, ID	4,539
IL, Lincoln	KILX	Logan County Airport: Lincoln, IL	696
IL, Chicago	KLOT	Romeoville, IL	760
IN, Evansville	KVWX	Owensville, IN	624
IN, Indianapolis	KIND	Indianapolis Intl. Airport	887
IN, Northern IN	KIWX	North Webster, IN	1,056
KS, Dodge City	KDDC	Dodge County Regional Airport	2,671
KS, Goodland	KGLD	Goodland, KS	3,716
KS, Topeka	KTWX	Alma, KS	1,415
KS, Wichita	KICT	Wichita Mid-Continental Airport	1,400
KY, Jackson	KJKL	Jackson, KY	1,462
KY, Louisville	KLVX	Fort Knox Military Reservation	833
KY, Paducah	KPAH	Barkley Regional Airport	506
LA, Lake Charles	KLCH	Lake Charles Regional Airport	94
LA, Slidell	KLIX	Slidell Airport	138
LA, Shreveport	KSHV	Shreveport Regional Airport	387
MA, Boston	KBOX	Taunton, MA	232
ME, Caribou	KCBW	Houlton, ME	860
ME, Portland	KGYX	Gray, ME	474
MI, Detroit	KDTX	White Lake, MI	1,186

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

* - Redundant RDA

**TABLE 3-1
NETWORK SITES**

Metropolitan Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
MI, Grand Rapids	KGRR	Kent County Intl. Airport	875
MI, Marquette	KMQT	Negaunee, MI	1,525
MI, N. Cent. Lower-MI	KAPX	Gaylord, MI	1,562
MN, Duluth	KDLH	Duluth, MN	1,542
MN, Minneapolis	KMPX	Chanhassen, MN	1,060
MO, Pleasant Hill	KEAX	Pleasant Hill, MO	1,093
MO, Springfield	KSGF	Springfield Regional Airport	1,375
MO, St. Louis	KLSX	Weldon Spring, MO	722
MS, Jackson	KDGX	Brandon, MS	609
MT, Billings	KBLX	Yellowstone County, MT	3,663
MT, Glasgow	KGGW	Valley County Intl. Airport	2,357
MT, Great Falls	KTFX	Great Falls, MT	3,779
MT, Missoula	KMSX*	Point Six Mtn., MT	7,904
NC, Morehead City	KMHX	Newport, NC	145
NC, Raleigh/Durham	KRAX	Clayton, NC	462
NC, Wilmington	KLTX	Shalotte, NC	145
ND, Bismarck	KBIS	Bismarck Muncpl. Airport	1,756
ND, Grand Forks/Fargo	KMVX	Mayville, ND	1,083
NE, Grand Island	KUEX	Blue Hill, NE	2,057
NE, North Platte	KLNX	County Airport Thedford, NE	3,068
NE, Omaha	KOAX	Valley, NE	1,262
NM, Albuquerque	KABX	Albuquerque, NM	5951
NV, Elko	KLRX *	Elko, NV	6,858
NV, Las Vegas	KESX	Opal Mtn: Nelson, NV	4,948

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

* - Redundant RDA

**TABLE 3-1
NETWORK SITES**

Metropolitan Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
NV, Reno	KRGX*	Nixon, NV	8,397
NY, Albany	KENX	East Berne, NY	1,907
NY, Binghamton	KBGM	Binghamton Reg. Airport	1,704
NY, Buffalo	KBUF	Greater Buffalo Intl. Airport	790
NY, Brookhaven	KOKX	Upton, NY	199
OH, Cincinnati	KILN	Wilmington, OH	1,170
OH, Cleveland	KCLE	Cleveland-Hopkins Airport	860
OK, Norman	KTLX	Midwest City, OK	1,278
OK, Tulsa	KINX	Inola, OK	749
OR, Medford	KMAX*	Mount Ashland, OR	7,561
OR, Pendleton	KPDT	Eastern Oregon Regional Airport	1,580
OR, Portland	KRTX	Scappoose, OR	1,686
PA, State College	KCCX	State College, PA	2,486
PA, Philadelphia	KDIX	Fort Dix: Manchester, NJ	230
PA, Pittsburgh	KPBZ	Coraopolis, PA	1266
SC, Charleston	KCLX	Grays, SC	211
SC, Columbia	KCAE	Columbia Metropolitan Airport	345
SC, Greer	KGSP	Greenville-Sprtb Airport: Greer, SC	1,054
SD, Aberdeen	KABR	Aberdeen Regional Airport	1,383
SD, Rapid City	KUDX	New Underwood, SD	3,130
SD, Sioux Falls	KFSD	Sioux Falls, SD	1,495
TN, Knoxville/TriCities	KMRX	Morristown, TN	1,435
TN, Memphis	KNQA	Millington Naval Air Station, TN	379
TN, Nashville	KOHX	Old Hickory, TN	676

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

* - Redundant RDA

**TABLE 3-1
NETWORK SITES**

Metropolitan Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
TX, Amarillo	KAMA	Amarillo International Airport	3,668
TX, Austin/San Antonio	KEWX	New Braunfels Muncpl. Airport	730
TX, Brownsville	KBRO	Brwnsvl/S.Padre Is. Intl. Airport	88
TX, Corpus Christi	KCRP	Corpus Christi Intl. Airport	142
TX, Dallas/Fort Worth	KFWS	Fort Worth, TX	764
TX, El Paso	KEPZ	County Airport SantaTeresa, NM	4,218
TX, Houston/Galvstn	KHGX	Dickinson, TX	115
TX, Lubbock	KLBB	Lubbock Intl. Airport	3,340
TX, Midland/Odessa	KMAF	Midland Intl. Airport	2,933
TX, San Angelo	KSJT	Mathis Field: San Angelo, TX	2,004
UT, Cedar City	KICX *	Blowhard Mtn: Iron County	10,714
UT, Salt Lake City	KMTX*	Promontory Pt: Box Elder County	6,574
VA, Sterling	KLWX	Sterling R&D Center: Sterling, VA	369
VA, Roanoke	KFCX	Coles Knob Floyd County	2,966
VA, Norfolk	KAKQ	Wakefield, VA	209
VT, Burlington	KCXX	Colchester, VT	431
WA, Seattle/Tacoma	KATX	Everett, WA	608
WA, Spokane	KOTX	Spokane, WA	2,449
WI, Green Bay	KGRB	Green Bay, WI	779
WI, La Crosse	KARX	La Crosse, WI	1,357
WI, Milwaukee	KMKX	Dousman, WI	1,023
WV, Charleston	KRLX	Ruthdale, WV	1,194
WY, Cheyenne	KCYS	Cheyenne, WY	6,193
WY, Riverton/Lander	KRIW	Riverton Regional Airport	5,633

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

* - Redundant RDA

**TABLE 3-2
SUPPLEMENTAL SITES**

Coverage Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
AL, Maxwell AFB	KMXX	Carrville, AL	514
AL, Fort Rucker	KEOX	Echo, AL	499
CA, Beale AFB	KBBX	Oroville, CA	221
CA, Edwards AFB	KEYX	Boron, CA	2,855
CA, Vandenberg AFB	KVBX	Orcutt, CA	1,321
DE, Dover AFB	KDOX	Ellendale, DE	164
FL, Eglin AFB	KEVX	Red Bay, FL	221
GA, Moody AFB	KVAX	South Stockton, GA	292
GA, Robins AFB	KJGX	Jeffersonville, GA	618
KY, Fort Campbell	KHPX	Trenton, KY	624
LA, Fort Polk	KPOE	Fort Polk, LA	473
MS, Columbus AFB	KGWX	Greenwood Springs, MS	557
ND, Minot AFB	KMBX	Deering, ND	1,591
NM, Cannon AFB	KFDX	Field Village, NM	4,698
NM, Holloman AFB	KHDX	Ruidoso, NM	4,270
NY, Fort Drum	KTYX	Montague, NY	1,960
OK, Altus AFB	KFDR	Frederick, OK	1,315
OK, Vance AFB	KVNX	Cherokee, OK	1,258
TX, Ft. Hood	KGRK	Granger, TX	603
TX, Dyess AFB	KDYX	Moran, TX	1,582
TX, Laughlin AFB	KDFX	Brackettville, TX	1,196

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

**TABLE 3-3
DOT NON-CONUS SITES**

Metropolitan Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
AK, Anchorage	PAHG*	Kenai, AK	356
AK, Bethel	PABC*	Bethel, AK	193
AK, Fairbanks	PAPD*	Pedro Dome, AK	2,707
AK, Sitka	PACG*	Biorka Island, AK	272
AK, King Salmon	PAKC*	King Salmon, AK	144
AK, Middleton Island	PAIH*	Middleton Island, AK	142
AK, Nome	PAEC*	Beam Road: Nome, AK	90
HI, Kamuela/Kohala	PHKM*	Kamuela, HI	3,926
HI, Molokai	PHMO*	Kukui Amikopala: Molokai, HI	1,444
HI, South Shore	PHWA*	Maalehu, HI	1,461
HI, South Kauai	PHKI*	McBryde Sugar Mill: Nimila, HI	293
PR, San Juan	TJUA*	Vereda Los Baldios: Cayey, PR	2,908

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

* All sites have a redundant RDA and RPG

**TABLE 3-4
DOD NON-CONUS SITES**

Metropolitan Area	Radar ICAO	RDA System Location	Antenna Elev. (Ft)
GUAM, Andersen AFB	PGUA	Barrigada Communication Facility	378
JAPAN, Kadena AB	RODN	Okinawa, Japan: White Beach	332
PORTUGAL, Lajes AB	LPLA	Santa Barabara Mtn, Isl.of Terceira	3,415
SOUTH KOREA, Camp Humphreys	RKSG	Camp Humphreys, ROK	133
SOUTH KOREA, Kunsan AB	RKJK	Kunsan Air Base: Radio Relay Hill	192

Updates for site information, along with other site data, can be found at: www.roc.noaa.gov/ssb/srchmain.asp

TABLE 3-5

CALCULATION OF ANTENNA ELEVATION

**Antenna
Elev. (Ft)**

ANTENNA ELEVATION (Feet): The elevation of the center of the WSR-88D antenna is expressed in feet above mean sea level (MSL). It is the sum of the antenna's center-point height above ground level (AGL) and the RDA site's terrain elevation.

For example, the WSR-88D antenna elevation for San Diego (KNKX) is;

- a. Antenna height (AGL) = RDA Tower + Antenna Pedestal Height.
- b. Antenna height (AGL) = 25.0 m + 4.7 m = 29.7 m.
- c. Antenna height (AGL) = (29.7 m) x 3.28 ft / m = 97.4 ft [Round to 97].
- d. Antenna Elevation (MSL) = Antenna height + RDA elevation.
- e. Antenna Elevation (MSL) = 97 ft + 955 ft = 1,052 ft MSL.

Values for the RDA site elevation and RDA tower height come from the National Implementation Staff (NIS) Site Reference Book. The value for antenna pedestal height was provided by the ROC.

CHAPTER 4

OPERATIONAL MODES, VOLUME COVERAGE PATTERNS, AND PRODUCTS

4.1 Introduction. This chapter outlines the WSR-88D operational modes [1], volume coverage patterns [2], and the full suite of WSR-88D products that may be generated.

4.2 Operational Modes. Two operational modes have been implemented: Clear Air and Precipitation. Each mode has one product mix and one or more volume coverage patterns. Selection of the operational mode is closely related to the detected coverage of precipitation. The Precipitation Detection Function (PDF) is designed to automatically determine if precipitation is occurring within 124 nm of the radar. The PDF examines reflectivity returns from the four lowest elevation angles, and compares them to the Precipitation Rate Threshold and an Area Threshold (the sum of the Precipitation Area Threshold and the Nominal Clutter Area Threshold). One of the following three Precipitation Categories is assigned each volume scan depending on which combination of thresholds are met or exceeded:

Category 0 - No precipitation detected within the past hour.

Category 1 - Significant precipitation detected.

Category 2 - No significant precipitation has been detected in the past hour and light precipitation is detected.

The Nominal Clutter Area (NCA) threshold is the only adaptable parameter of the Precipitation Detection Function that may be changed under authority of the Unit Radar Committee (URC). The routine practice of adjusting the nominal clutter area should be based on policies set forth by your local URC.

When significant precipitation is detected and exceeds the threshold values, Precipitation Category 1 is assigned. When Precipitation Category 1 has not been detected within the past hour and light precipitation exceeds the threshold values, Precipitation Category 2 is assigned. When no precipitation is detected for one hour, the Precipitation Category is 0. [3]

[1] Operational Mode -- A combination of one or more volume coverage patterns and product lists designed to better observe one or more features in a given meteorological environment.

[2] Volume Coverage Pattern -- An automated method that repetitively scans the atmosphere through the same set sequence of predefined elevation angles, antenna rotation rates, and pulse characteristics. This given sequence, called a volume scan, is completed in 4.1, 5, 6, or 10 minutes (subject to change in future software builds), and then repeated.

[3] As of RPG Build 5, the Precipitation Processing System (PPS) algorithms will no longer key off the PDF in determining the rainfall status. Instead, a somewhat analogous function, internal to the PPS, that assesses rainfall areas on the assembled Hybrid Scan will be used to determine start/stop times of distinct precipitation events.

4.2.1 Mode A -- Precipitation Mode. This mode should be used when significant weather echoes are present or severe weather is occurring or is anticipated. Usually, this mode will have been selected automatically due to the detection of Precipitation Category 1. At times, however, such as the early, mid-level formation of convective echoes, the RPG Human-Computer Interface (HCI) operator may choose to enter the Precipitation Mode manually.

4.2.2 Mode B -- Clear-Air Mode. This mode may be used when there is no detectable precipitation (Precipitation Category 0) or when precipitation intensity and areal extent are small (Precipitation Category 2). The RPG software will not allow a change to Clear-Air Mode until Precipitation Category 1 has not been detected for at least one hour. Since there is not an automatic switch to a Mode B VCP, the operator must use the RPG HCI to effect a change to the Clear-Air Mode from Precipitation Mode.

4.3 Volume Coverage Patterns. During operations, the antenna is controlled by automatic scanning programs. Volume coverage patterns (VCPs) are matched to an operational mode to optimize product generation for given meteorological situations; the various VCPs are defined in Part C of this handbook. In each operational mode, scanning is continuous. Principal users are informed of the radar operational mode and the VCP in use through the system status messages.

4.3.1 Volume Coverage Patterns 31 and 32. Both of these VCPs are used in the Clear-Air Mode to optimize the sensitivity of the WSR-88D. The VCP 31 (long pulse) provides a better signal-to-noise ratio permitting lower reflectivity returns to be detected, while VCP 32 (short pulse) provides a higher unambiguous velocity.

4.3.2 Volume Coverage Patterns 11 and 21. These VCPs are used in the Precipitation Mode to better sample the vertical structure of convective weather echoes and to provide better temporal resolution. VCP 11 provides better vertical sampling of weather echoes near the antenna than VCP 21 and is usually preferred in situations where convective precipitation is within 60 nmi of the antenna.

4.3.3 Volume Coverage Pattern 12. This VCP, added in 2004 with Build 5, has the same number of elevation angles as VCP 11. However, denser vertical sampling at lower elevation angles will provide better vertical definition of storms, improve detection capability of radars impacted by terrain blockage for better rainfall and snowfall estimates, result in more storms being identified, and provide quicker updates.

4.3.4. Volume Coverage Pattern 121. This VCP, added in 2004 with Build 5, has the same elevation angles as VCP 21, but more scans. This VCP implements the multi-pulse repetition frequency detection algorithm (MPDA) which will help mitigate range/velocity aliasing (the Doppler Dilemma).

**TABLE 4-1
VOLUME COVERAGE PATTERN DESCRIPTION**

Volume Coverage Pattern Number	Number Of Azimuthal Scans	Number Of Different Elevation Angles	Time To Complete (Minutes)
11	16	14	5
12	17	14	4.1
21	11	9	6
31	7	5	10
32	7	5	10
121	20	9	5

4.4 WSR-88D Product Suite. Table 4-2 provides brief descriptions of every WSR-88D product. Products are initiated for generation through one of several means: through the RPG Product Generation Table, Routine Product Set (RPS) lists, alert-product pairing, and through one-time requests from associated users. The specific products that constitute the baseline Product Suite for each weather mode are defined in the WSR-88D Operator Handbook, Guidance on Adaptable Parameters - RPG. Additions to supplement the Product Suite are permissible as long as the integrity of the baseline is maintained. The products listed in Table 4-2 are current as of RPG software Build 5 (March 2004 release).

**TABLE 4-2
PRODUCT DESCRIPTION**

PROD ID	PROD NUM	DATA LEVELS	COVERAGE (nmi)	RESOLUTION (nmi or see key)	PRODUCT NAME AND DESCRIPTION
R	16	8	0 - 124	.54 x 1E	Reflectivity.
R	17	8	0 - 248	1.1 x 1E	Reflectivity.
R	18	8	0 - 248	2.2 x 1E	Reflectivity.
R	19	16	0 - 124	.54 x 1E	Reflectivity.
R	20	16	0 - 248	1.1 x 1E	Reflectivity.
R	21	16	0 - 248	2.2 x 1E	Reflectivity.
V	22	8	0 - 32	.13 x 1E	Mean Radial Velocity.
V	23	8	0 - 62	.27 x 1E	Mean Radial Velocity.
V	24	8	0 - 124	.54 x 1E	Mean Radial Velocity.
V	25	16	0 - 32	.13 x 1E	Mean Radial Velocity.
V	26	16	0 - 62	.27 x 1E	Mean Radial Velocity.
V	27	16	0 - 124	.54 x 1E	Mean Radial Velocity.
SW	28	8	0 - 32	.13 x 1E	Spectrum Width.
SW	29	8	0 - 62	.27 x 1E	Spectrum Width.
SW	30	8	0 - 124	.54 x 1E	Spectrum Width.
USP	31	16	0 - 124	1.1 x 1 E	User Selectable Precipitation. Can be adapted for the period of accumulation.
DHR	32	256	0 - 124	.54 x 1 E	Digital Hybrid Reflectivity. Not available for PUPs or for RPCCDS.
HSR	33	16	0 - 124	.54 x 1 E	Hybrid Scan Reflectivity.
CFC	34	8	0 - 124	.54 x 1.4 E	Clutter Filter Control. Generated when clutter suppression definition changes.
CR	35	8	0 - 124	.54 x .54	Composite Reflectivity.

**TABLE 4-2
PRODUCT DESCRIPTION**

PROD ID	PROD NUM	DATA LEVELS	COVERAGE (nmi)	RESOLUTION (nmi or see key)	PRODUCT NAME AND DESCRIPTION
CR	36	8	0 - 248	2.2 x 2.2	Composite Reflectivity.
CR	37	16	0 - 124	.54 x .54	Composite Reflectivity.
CR	38	16	0 - 248	2.2 x 2.2	Composite Reflectivity.
ET	41	16	0 - 124	2.2 x 2.2	Echo Tops. Min=5,000 ft, Max=70,000 ft MSL.
SWR	43	16	0 - 124	.54 x 1E	Severe Weather Analysis -- Reflectivity. Presentation area is 27 nmi x 27 nmi and is centered on: (a) alerting phenomenon or, (b) user selected coordinates.
SWV	44	16	0 - 124	.13 x 1E	Severe Weather Analysis -- Velocity. See SWR (ID #43) description.
SWW	45	16	0 - 124	.13 x 1E	Severe Weather Analysis -- Spectrum Width. See SWR (ID# 43) description.
SWS	46	16	0 - 124	.27 x 1E	Severe Weather Analysis -- Radial Shear. See SWR (ID#43) description, above.
SWP	47	4	0 - 124	n-a	Severe Weather Probability. Default presentation 'box' is 15.1 nmi x 15.1 nmi.
VWP	48	30	16 (default value)	1,000 ft (z)	VAD Wind Profile. Barbs show speeds to nearest 5 kt. Height (every 1000 ft) is plotted on z-axis and time (up to 11 volume scans) is plotted on x-axis.
RCS	50	16	0 - 124	.54 x .27(z)	Cross Section -- Reflectivity. Min=0 ft, Max=70,000 ft MSL .
VCS	51	16	0 - 124	.54 x .27(z)	Cross Section -- Velocity. Min=0 ft, Max=70,000 ft MSL.

**TABLE 4-2
PRODUCT DESCRIPTION**

PROD ID	PROD NUM	DATA LEVELS	COVERAGE (nmi)	RESOLUTION (nmi or see key)	PRODUCT NAME AND DESCRIPTION
SRR	55	16	0 - 124	.27 x 1E	Storm Relative Mean Radial Velocity--Region. See notes for SRM (#56), below. The presentation area is 27 nmi x 27 nmi centered on operator defined location.
SRM	56	16	0 - 124	.54 x 1E	Storm Relative Mean Radial Velocity--Map. Derived from vector average of all identified storms or vector input by operator. Presentation area is 0 to 124 nmi.
VIL	57	16	0 - 124	2.2 x 2.2	Vertically Integrated Liquid Water.
STI	58	6	0 - 186	n-a	Storm Tracking Information. Graphic product with 15 minute position intervals.
HI	59	5	0 - 124	n-a	Hail Index. Includes overlay to show probability and max hail size per storm.
M	60	3	0 - 124	n-a	Mesocyclone. Includes overlay for identified storms' data.
TVS	61	n-a	0 - 124	n-a	Tornadic Vortex Signature. Includes overlay for identified storms' data.
SS	62	n-a	0 - 248	n-a	Storm Structure. Table generated each VCP.
LRA	63	8	248 x 248	2.2 x 2.2	Layer Composite Reflectivity – Average. Low Layer.
LRA	64	8	248 x 248	2.2 x 2.2	Layer Composite Reflectivity--Average. Mid Layer.
LRM	65	8	248 x 248	2.2 x 2.2	Layer Composite Reflectivity--Maximum. Low Layer.
LRM	66	8	248 x 248	2.2 x 2.2	Layer Composite Reflectivity--Maximum. Mid Layer.

**TABLE 4-2
PRODUCT DESCRIPTION**

PROD ID	PROD NUM	DATA LEVELS	COVERAGE (nmi)	RESOLUTION (nmi or see key)	PRODUCT NAME AND DESCRIPTION
APR	67	8	248 x 248	2.2 x 2.2	Layer Composite Reflectivity--AP Removed. Low Layer.
UAM	73	n-a	n-a	n-a	User Alert Message. Generated upon alert activation.
RCM	74	9	0 - 248	1/16 x 1/16 L	Radar Coded Message. Generated near HH:20 & HH:50 UTC. Derived from the IRM product . See the IRM (ID #83) description, below.
FTM	75	n-a	n-a	n-a	Free Text Message. Messages can be generated at MSCF and RPG.
OHP	78	16	0 - 124	1.1 x 1E	One-Hour Precipitation.
THP	79	16	0 - 124	1.1 x 1E	Three-Hour Precipitation.
STP	80	16	0 - 124	1.1 x 1E	Storm-Total Precipitation.
DPA	81	256	0 - 124	1/40 x 1/40 L	Digital Precipitation Array. A one-hour accumulation product made with OHP.
SPD	82	8	0 - 124	1/4 x 1/4 L	Supplemental Precipitation Data. Alphanumeric with rain gage values and times.
VAD	84	8	16 (default value)	n-a	Velocity Azimuth Display. Product is available for altitudes specified by VWP product (#48).
RCS	85	8	0 - 124	.54 x .27(z)	Cross Section -- Reflectivity.
VCS	86	8	0 - 124	.54 x .27(z)	Cross Section -- Velocity.
CS	87	16	124 x 124	'adaptable'	Combined Shear.
LRA	89	8	248 x 248	2.2 x 2.2	Layer Composite Reflectivity--Average. High Layer.

**TABLE 4-2
PRODUCT DESCRIPTION**

PROD ID	PROD NUM	DATA LEVELS	COVERAGE (nmi)	RESOLUTION (nmi or see key)	PRODUCT NAME AND DESCRIPTION
LRM	90	8	248 x 248	2.2 x 2.2	Layer Composite Reflectivity--Maximum. High Layer.
DBV	93	256	lesser of 62 nmi or 18K ft AGL	.54 x 1E	ITWS Digital Base Velocity
DR	94	256	0 - 248	.54 x 1E	Base Reflectivity Data Array
CRE	95	8	0 - 124	.54 x 1E	Composite Reflectivity Edited for AP
CRE	96	8	0 - 248	2.2 x 2.2	Composite Reflectivity Edited for AP
CRE	97	16	0 - 124	.54 x .54	Composite Reflectivity Edited for AP
CRE	98	16	0 - 248	2.2 x 2.2	Composite Reflectivity Edited for AP
DV	99	256	0 - 124	.13 x 1E	Base Velocity Data Array
CLR	132	11	0 - 124	.54 x 1E	Clutter Likelihood Reflectivity
CLD	133	12	0 - 124	.54 x 1E	Clutter Likelihood Doppler
DVL	134	256	0 - 248	.54 x 1E	High Resolution Digital Vertically Integrated Liquid Water
EET	135	71	0-124	0.54	Enhanced Echo Top
SO	136	n-a	n-a	n-a	Superob: NCEP Winds Model Initialization
ULR	137	16	0 - 124	.54 x 1E	User Selectable Layer Composite Reflectivity
DSP	138	256	0 - 124	1.1 x 1E	Storm Total Rainfall Accumulation (Digital Storm Product)

**TABLE 4-2
PRODUCT DESCRIPTION**

PROD ID	PROD NUM	DATA LEVELS	COVERAGE (nmi)	RESOLUTION (nmi or see key)	PRODUCT NAME AND DESCRIPTION
MRU	139	3	0 - 124	n-a	Mesocyclone Rapid Update
MD	141	3	0 - 124	n-a	Mesocyclone Detection
TRU	143	n-a	0 - 124	n-a	Tornadic Vortex Signature Rapid Update

n-a = not applicable.

z = vertical

The products listed in this table are current as of RPG software Build 5 (March 2004 release).

KEY FOR TABLE 4-2

<u>PROD ID</u>	PRODUCT IDENTIFIER: The official one, two, or three letter abbreviations used by the WSR-88D system and displayed on WSR-88D products.
<u>PROD NUM</u>	PRODUCT NUMBER: The official identification number assigned to WSR-88D products. Product numbers are recognized by the system software.
<u>DATA LEVELS</u>	DATA LEVELS: The number of gradations that display the magnitude of data in a color indexed graphical format. Some alphanumeric products have multiple categories of information (e.g., severe weather probability). The number of categories is expressed as the number of data levels.
<u>COVERAGE</u>	RANGE OF COVERAGE: The geographical scope of coverage for a given product. There are three types of product formats; polar, cartesian, and grid-based. The areal extent for polar and grid-based products is indicated with a polar range limit (e.g., 248 nmi). Cartesian products' areal extent is described by x-axis and y-axis lengths (e.g., 124 nmi x 124 nmi).
<u>RESOLUTION</u>	DATA RESOLUTION: Standard units of measure describe the size of the products' discrete data elements. The type of units used (e.g., nmi, arcdegree, grid fraction) is a function of a product's format. Product formats are: polar, cartesian, and grid-based. The limited-area fine mesh (LFM) grid is a standard reference for the radar coded message products. 1/40 L: Approximately 2.2 nmi x 2.2 nmi. The 2.2 nmi length is 1/40 of the LFM grid-point separation. 1/16 L: Approximately 5.4 nmi x 5.4 nmi. The 5.4 nmi length is 1/16 of the LFM grid-point separation. 1/4 L: Approximately 22 nmi x 22 nmi. The 22 nmi length is 1/4 of the LFM grid-point separation.
<u>PRODUCT NAME AND DESCRIPTION</u>	The full name of product followed by pertinent information.

CHAPTER 5

ARCHIVING

5.1 Introduction. The WSR-88D system has the capability to provide for the archiving of data and products at four functional locations. The locations are identified as Archive Levels I, II, III, and IV, respectively. The following sections, exclusive of the final section, provide a brief description of each level and potential utilization of data archived at each level. The final section provides information pertaining to product retention at the National Climatic Data Center (NCDC).

5.2 Archive Level I. The Archive Level I interface is located at the RDA. Data available are the analog, time-domain output of the receiver. Information regarding synchronization, calibration, date, time, antenna position, and status is also available at this level. However, Archive Level I is not used operationally. Archive Level I data is used for RDA system diagnostics and input for signal processor optimization studies.

5.3 Archive Level II. Archive Level II data are the digital base data output from the signal processor. The output also includes status information required to properly interpret the data (e.g., information on synchronization, calibration, date, time, antenna position, clutter and notchwidth maps, operational mode). Archive Level II data are used for many purposes including: support of operational, maintenance and developmental activities at the ROC; activities directed toward algorithm and product enhancement; and research by universities. The only Level II data archived are those sent to the NCDC by the NWS WSR-88D Level II Central Collection and Distribution Network, reference section 2.4.2.

5.4 Archive Level III. Archive Level III data are the output of the RPG. Archive Level III data are continuously transmitted from DOC WSR-88D systems to the NCDC via the Advanced Weather Interactive Processing System (AWIPS).

The *WSR-88D Operator Handbook, Guidance on Adaptable Parameters-RPG*, defines the products and the frequency at which these products are generated for transmission to the NCDC. The handbook can be obtained at the following URL:
<http://www.roc.noaa.gov/ssb/sysdoc/Operations.asp>.

5.5 Archive Level IV. Archive Level IV data are the output data of the RPG. The Archive Level IV interface is located at the PUP. All DOD sites with a PUP will perform Archive Level IV archiving for local training, studies, accident investigation, and other purposes as required. DoD sites with an OPUP have an Archive Level IV-like capability. At NWS sites, the AWIPS has an Archive Level IV-like capability.

5.6 Retention by National Climatic Data Center. The *WSR-88D Operator Handbook, Guidance on Adaptable Parameters-RPG* lists the products that shall be archived for Mode A (Precipitation) and Mode B (Clear-air) respectively, at the RPG (Archive Level III) by all Network Sites at the frequency shown. The handbook can be obtained at the following URL: <http://www.roc.noaa.gov/ssb/sysdoc/Operations.asp>.

As an extension of sites sending the narrowband data, beyond Level III, to the RPCCCDS, the NCDC receives, archives, and makes these products and data available upon request. The list of these products in the NCDC archives is available at the following URL: <http://www4.ncdc.noaa.gov/cgi-win/wwcgi.dll?WWDI~RadarList~N>. The data are collected for all WSR-88D sites except for the 4 remote DOD sites (Lajes AB, Kadena AB, Camp Humphreys, and Kunsan AB).

Archive Level II and Archive Level III data are sent to the NCDC for permanent retention. WSR-88D archive data information can be obtained from the NCDC home page (<http://www.ncdc.noaa.gov>) and clicking on 'Radar.'

CHAPTER 6

ADAPTABLE PARAMETER CHANGE AUTHORITY

6.1 Introduction. The WSR-88D's design includes thousands of parameters that permit each WSR-88D system to be adapted to certain geographical and meteorological conditions to support operational requirements. Since the WSR-88D is operated to satisfy the integrated needs of the principal users and to support the national radar network, centralized control of many of the system and meteorological parameters is required to ensure a baseline operational standard. However, a subset of these parameters was designed specifically to address the local operational needs. For this reason the principal user agencies agreed to categorize a number of WSR-88D adaptable parameters into three levels of change authority (LOCA) as defined in section 6.2. This was done, primarily, to ensure the proper LOCA use of these adaptable parameters. As defined, each of these three LOCA categories permits the modification of WSR-88D hardware and software through a controlled process.

Official guidance on WSR-88D adaptable parameters is documented by the *WSR-88D Operator Handbook, Guidance on Adaptable Parameters, Volumes II-IV*. RPG parameters, are comprehensively categorized by their LOCA in Volume IV, PUP parameters are comprehensively enumerated in Volume II, and RDA system parameters are covered in Volume III and RPG parameters are covered in Volume IV. Volumes II and IV discuss the default and alternate settings that optimize the control of algorithms and the quality of WSR-88D products and communications.

6.2 Levels of Change Authority. The adaptable parameters have been grouped according to the level of approval that is necessary before the parameter's value can be changed. These groupings are intended to give maximum flexibility in operational use of the WSR-88D while ensuring that agency operations are not jeopardized and the system remains stable.

6.2.1 Radar Operations Center. Through the Adaptable Parameter Working Group (APWG) the ROC shall determine the general validity and range of adaptable parameter values for changes that affect the technical and scientific characteristics of WSR-88D data acquisition and algorithmic processing. In addition, the ROC shall be authorized to determine, specifically, the values for the aforementioned default adaptable parameter values for WSR-88D equipment owned by the DOD, DOT, and the DOC. Since the APWG shall remain subordinate to the NEXRAD Program Management Committee (NPMC), the ROC level of change authority shall reflect the NPMC's position on triagency policy in WSR-88D operations.

6.2.2 Unit Radar Committee. Each Unit Radar Committee (URC) shall be authorized to change their WSR-88D system's adaptable parameter values and establish adaptation parameter policy for the principal users within the URC. Types of changes that a single URC is authorized to implement shall include the "fine-tuning" needed to meet local operational requirements, seasonal changes, and local climatological characteristics.

6.2.3 Agency. The agency is the principal user agency (DOC, DOD, or DOT) that controls the involved hardware and software. Each agency is authorized to change the range of adaptable parameter values, change default values, and establish WSR-88D adaptable parameter policy in order to meet agency-specific mission requirements and criteria. Changes that a single agency is authorized to implement may involve user passwords, meteorological algorithm parameters, and certain telecommunications settings.

APPENDIX A

ACRONYMS AND ABBREVIATIONS

AB	- Air Base
AFB	- Air Force Base
AGL	- Above Ground Level
APWG	- Adaptable Parameter Working Group
ATCSCC	- Air Traffic Control Systems Command Center
AWC	- Aviation Weather Center
AWIPS	- Advanced Weather Interactive Processing System
CFC	- Clutter Filter Control
CONUS	- Conterminous United States
CR	- Composite Reflectivity
CRC	- Composite Reflectivity Contour
CS	- Combined Shear
DHR	- Digital Hybrid Reflectivity
DOC	- Department of Commerce
DOD	- Department of Defense
DOT	- Department of Transportation
DPA	- Digital Precipitation Array
DSP	- Digital Storm Product
Elev	- Elevation
ET	- Echo Tops
FAA	- Federal Aviation Administration
FMH	- Federal Meteorological Handbook
Ft	- Foot
FTM	- Free Text Message
FTP	- File Transfer Protocol
HCI	- Human Computer Interface
HI	- Hail Index
HPC	- Hydrometeorological Prediction Center

ICAO	- International Civil Aviation Organization
ICMSSR	- Interdepartmental Committee for Meteorological Services and Supporting Research
ID	- Identifier
ITWS	- Integrated Terminal Weather System
LFM	- Limited Area Fine Mesh
LOCA	- Level of Change Authority
LRA	- Layer Composite Reflectivity - Average
LRM	- Layer Composite Reflectivity - Maximum
m	- Meter
M	- Mesocyclone
MPC	- Marine Prediction Center
MPDA	- Multi-Pulse Repetition Frequency Detection Algorithm
MSCF	- Master System Control Function
MSL	- Mean Sea Level
NA	- Non-Associated; Not Applicable
NCDC	- National Climatic Data Center
NCEP	- National Centers for Environmental Prediction
NEXRAD	- Next Generation Weather Radar
nmi	- Nautical Mile
NPC	- NEXRAD Program Council
NWS	- National Weather Service
OFCM	- Office of the Federal Coordinator for Meteorological Services and Supporting Research
OHP	- One-Hour Precipitation Accumulation
OWS	- Operational Weather Squadron
PDF	- Precipitation Detection Function
PMC	- Program Management Committee
PUES	- Principal User External System
PUP	- Principal User Processor
R	- Reflectivity
RCM	- Radar Coded Message
RCS	- Cross Section - Reflectivity
RDA	- Radar Data Acquisition (System)

RFC	- River Forecast Center
ROC	- Radar Operations Center
RPCCDS	- Radar Product Central Collection Dissemination Service
RPG	- Radar Product Generator
RPS	- Routine Product Set
SCIT	- Storm Cell Identification and Tracking
SPC	- Storm Prediction Center
SPD	- Supplemental Precipitation Data
SRM	- Storm-Relative Mean Radial Velocity, Map
SRR	- Storm-Relative Mean Radial Velocity, Region
SS	- Storm Structure
STI	- Storm Tracking Information
STP	- Storm-Total Precipitation Accumulation
SW	- Spectrum Width
SWP	- Severe Weather Probability
SWR	- Severe Weather Analysis - Reflectivity
SWS	- Severe Weather Analysis - Shear
SWV	- Severe Weather Analysis - Velocity
SWW	- Severe Weather Analysis - Spectrum Width
THP	- Three-Hour Precipitation Accumulation
TPC	- Tropical Prediction Center
TVS	- Tornadic Vortex Signature
UAM	- User Alert Message
ULR	- User Selectable Layer Composite Reflectivity
URC	- Unit Radar Committee
URL	- Uniform Resource Locator
USP	- User Selectable Precipitation
V	- Velocity
VAD	- Velocity Azimuth Display
VCP	- Volume Coverage Pattern
VCS	- Cross Section - Velocity
VIL	- Vertically Integrated Liquid
VWP	- Velocity Azimuth Display Wind Profile
WG/DRMO	- Working Group for Doppler Radar Meteorological Observations
WSR-88D	- Weather Surveillance Radar - 1988, Doppler

This Page Intentionally Left Blank

APPENDIX B

GLOSSARY

Adaptable Parameter: Generally, data related to a specific WSR-88D system. These data may consist of meteorological or hydrological parameters or of geographic boundaries, political boundaries, system configuration, telephone numbers, or other like data. Such data may be generated at either a centralized location or locally.

Associated Principal User: A principal user linked to a WSR-88D system with a dedicated telecommunication line.

Base Data: Those digital fields of reflectivity, mean radial velocity, and spectrum width data in spherical coordinates provided at the finest resolution available from the radar.

Conterminous United States: Those states of the United States enclosed within one common boundary. The conterminous 48 states of the United States is abbreviated 'CONUS'.

Data Resolution: The resolution of the base data as produced by the signal processor, nominally 0.54 nautical mile (1 kilometer) x 1 degree in azimuth x 1 degree in elevation for reflectivity values and 0.13 nautical mile (0.25 kilometer) x 1 degree x 1 degree for velocity values.

Default Value: A setting or value that will be used in a given software program unless changed.

Echoes: Areas of radar reflectivity that are visible in the WSR-88D products that may represent meteorological or non-meteorological phenomena.

Elevation Angle: The angle the WSR-88D antenna subtends to the horizontal plane. This value can vary from 0E to + 60E.

External User: Anyone other than a Principal User who has access to WSR-88D products, e.g., information service companies, broadcast meteorologists, aviation interests, industrial meteorologists, other government agencies, and universities.

Mesocyclone: A 3-dimensional region in a storm that rotates (usually cyclonically) and is closely correlated with severe weather.

National Weather Radar Network: Consists of WSR-88D sites dispersed throughout the CONUS.

Network Site: A DOC WSR-88D site in the CONUS that continuously collects, collates, and makes available radar data and products in support of the national weather radar network.

NEXRAD Program Council: Composed of a representative from each of the DOC, DOD, and DOT, and the Federal Coordinator for Meteorological Services and Supporting Research.

Non-Associated Principal User: A principal user with access to a WSR-88D system through means of dial telecommunication.

Non-Network Site: A non-CONUS DOD site or a non-CONUS DOT site.

Operational Mode: A combination of one or more volume coverage patterns and product lists designed to better represent one or more features in a given meteorological environment.

Principal User: Principal users are the NWS, the Air Force, the Naval Meteorology and Oceanography Command, the Marine Corps Weather Service Units, and the FAA.

NEXRAD Program Management Committee: A NEXRAD Program triagency organization comprised of representatives of DOC (NWS), DOD (Air Force Weather Agency), and DOT (FAA). Its responsibilities encompass all WSR-88D operational aspects (e.g., WSR-88D operations, maintenance, logistics, documentation, and training) to ensure that the common and unique agency concerns are addressed.

Radial Velocity: The component of motion of the target toward or away from the radar.

Reflectivity: The measure of the efficiency of a target in intercepting and returning radio energy. With hydrometeors it is a function of the drop size distribution, number of particles per unit volume, physical state (ice or water), shape, and aspect.

Spectrum Width: A measure of dispersion of velocities within the radar sample volume.

Supplemental Site: A DOD WSR-88D site in the CONUS. It continuously collects, collates, and makes available radar data and products in support of the DOD.

Tornadic Vortex Signature: The radar signature of a vortex that is indicative of a tornado or tornadic circulation.

Unit Radar Committee: A coordinating committee, established by the MOA for Interagency Operation of the WSR-88D, composed of representatives of each principal user agency associated with a particular WSR-88D system.

